

PRV

Pressure Reducing Valve Integrated with Relief Valve

Flowtek

<http://www.flowtek-ltd.com/>
E-mail: clamp.well@msa.hinet.net

Application

When you want to use lower pressure in a higher pressure system, you can select pressure reducing valve to use lower pressure clamp cylinder or other device..

Function

The pressure reducing valve is integrated with a relief valve inside, the function is stable.



(Direct Acting)

<p>Ordering Code: PRV-40-X-Y-Z</p> <p style="text-align: center;">Port size G3/8"</p> <p style="text-align: center;">Mounting Holes: $\Phi 8.7$mm. diameter through hole 2 places. Manifold O-ring : P-10</p> <p style="text-align: right;">1.Reduced Pressure 2.Inlet 3.Tank</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">TECHNICAL DATA</th> </tr> </thead> <tbody> <tr> <td>Max.Operating pressure:</td> <td>350 bar</td> </tr> <tr> <td>Rated flow:</td> <td>40 l/min</td> </tr> <tr> <td>Cavity-Tooling:</td> <td>11A-3</td> </tr> <tr> <td>Installation torque:</td> <td>40-50 Nm</td> </tr> <tr> <td>Weight:</td> <td>0.19 kg</td> </tr> </tbody> </table>	TECHNICAL DATA		Max.Operating pressure:	350 bar	Rated flow:	40 l/min	Cavity-Tooling:	11A-3	Installation torque:	40-50 Nm	Weight:	0.19 kg														
TECHNICAL DATA																											
Max.Operating pressure:	350 bar																										
Rated flow:	40 l/min																										
Cavity-Tooling:	11A-3																										
Installation torque:	40-50 Nm																										
Weight:	0.19 kg																										
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 5%; text-align: center;">X</th> <th style="text-align: center;">OPERATION</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">30</td> <td style="text-align: center;">Standard Type</td> </tr> <tr> <td colspan="2">Maximum Leakage (33 cc/min./70 bar)</td> </tr> </tbody> </table>	X	OPERATION	30	Standard Type	Maximum Leakage (33 cc/min./70 bar)																					
X	OPERATION																										
30	Standard Type																										
Maximum Leakage (33 cc/min./70 bar)																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 5%; text-align: center;">Y</th> <th style="text-align: center;">SPRINGS</th> </tr> <tr> <th colspan="2" style="text-align: center;">ADJUSTMENT RANGES</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">A</td> <td>35 to 210 bar (50 bar Standard Setting)</td> </tr> <tr> <td style="text-align: center;">B</td> <td>3.5 to 105 bar (14 bar Standard Setting)</td> </tr> <tr> <td style="text-align: center;">D</td> <td>1.7 to 55 bar (14 bar Standard Setting)</td> </tr> <tr> <td style="text-align: center;">E</td> <td>1.7 to 28 bar (14 bar Standard Setting)</td> </tr> <tr> <td style="text-align: center;">H</td> <td>7 to 210 bar (50 bar Standard Setting)</td> </tr> <tr> <td style="text-align: center;">S</td> <td>1.7 to 14 bar (7 bar Standard Setting)</td> </tr> <tr> <td style="text-align: center;">W</td> <td>50 to 315 bar (70 bar Standard Setting)</td> </tr> </tbody> </table>	Y	SPRINGS	ADJUSTMENT RANGES		A	35 to 210 bar (50 bar Standard Setting)	B	3.5 to 105 bar (14 bar Standard Setting)	D	1.7 to 55 bar (14 bar Standard Setting)	E	1.7 to 28 bar (14 bar Standard Setting)	H	7 to 210 bar (50 bar Standard Setting)	S	1.7 to 14 bar (7 bar Standard Setting)	W	50 to 315 bar (70 bar Standard Setting)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 5%; text-align: center;">Z</th> <th style="text-align: center;">OPTIONS</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">L</td> <td>Leakproof hex. socket screw. </td> </tr> <tr> <td style="text-align: center;">LP</td> <td>Leakproof hex. socket screw. With stainless steel external metal components </td> </tr> <tr> <td style="text-align: center;">C</td> <td>Stainless Steel Tamper Resistant Cover. </td> </tr> </tbody> </table>	Z	OPTIONS	L	Leakproof hex. socket screw.	LP	Leakproof hex. socket screw. With stainless steel external metal components	C	Stainless Steel Tamper Resistant Cover.
Y	SPRINGS																										
ADJUSTMENT RANGES																											
A	35 to 210 bar (50 bar Standard Setting)																										
B	3.5 to 105 bar (14 bar Standard Setting)																										
D	1.7 to 55 bar (14 bar Standard Setting)																										
E	1.7 to 28 bar (14 bar Standard Setting)																										
H	7 to 210 bar (50 bar Standard Setting)																										
S	1.7 to 14 bar (7 bar Standard Setting)																										
W	50 to 315 bar (70 bar Standard Setting)																										
Z	OPTIONS																										
L	Leakproof hex. socket screw.																										
LP	Leakproof hex. socket screw. With stainless steel external metal components																										
C	Stainless Steel Tamper Resistant Cover.																										